

PROTECTS SORBENT TRAPS FROM PARTICULATE & MOISTURE

Stainless steel and C276 alloy shields mount on Apex dual stream sorbent trap mercury probe. Specifically designed for use in high particulate/moisture gas streams. Available in two sizes: 6" Long x 2" O.D. and 4.5" Long x 3/4" O.D. Diameter.

- Reduces Sorbent Trap Plugging when Used in High Particulate & High Moisture Environments.
- Easily Installed on Existing Mercury Probes.
- Simple Removal for Access to Sorbent Traps.



HGP-SHIELD-S-EXT-6 Stainless Steel or HGP-SHIELD-C-EXT-6 C276 Alloy Shields.



10MMNU2-S-EXT4D and 10MMNU2-S-EXT4 Stainless Steel Shields.

Mercury Sorbent Trap Shields

Part Number	Description
HGP-SHIELD-S-EXT-6	Stainless Steel Trap Shield , 6" Length x 2" O.D. Diameter. <i>Recommended for short sampling runs, such as those required by Method 30B.</i>
HGP-SHIELD-C-EXT-6	C276 Alloy Trap Shield , 6" Length x 2" O.D. Diameter. <i>Recommended for corrosive environments and long continuous sampling runs (5 to 7 days).</i>
10MMNU2-S-EXT4D	Stainless Steel Trap Shield (with holes) - Particulate shield for 10mm sorbent trap with holes, stainless steel nuts and tubing, 4.5" Length x 3/4" O.D. <i>Requires 2 per probe.</i>
10MMNU2-S-EXT4	Stainless Steel Trap Shield (without holes) - Particulate shield for 10mm sorbent trap without holes, stainless steel nuts and tubing, 4.5" Length x 3/4" O.D. <i>Requires 2 per probe.</i>